

The Excellent & Professional Power Amplifier



MA-1200 Specification

Audio Output	600W+600W 4~8 ohm
Frequency Response	20Hz to 20kHz (+0, -0.2dB, 4 ohms)
Gain	35dB at maximum ATT setting, 2ch
Gain	41dB at maximum ATT setting, Bridge
Sensitivity	775mV 0dBm
Impedance	20k ohms Bal./10k ohms Unbalance
Signal to Noise Ratio	+102dB IHF-A, Short circuit
Total Harmonic Distortion	0.01% 20kHz, 4 ohms
Load Impedance	4 ohms to 16 ohms 2 CH. 8 ohms to 32 ohms Bridge
Damping Factor	More than 470 1kHz, 8 ohms More than 150 20Hz~20kHz, 8 ohms

Crosstalk	More than 90dB 1kHz, 8 ohms, rated output. More than 75dB 20Hz~20kHz, 8 ohms, rated output
Cooling System	Forced air cooling
Input Terminal	Female XLR type with pin-assignment switch, 1/4" phone jack
Output Terminal	Speakon output, 1/4" phone for input-through output
Power Requirements	AC 110V, 60Hz 720W
Dimensions (WxHxD)	20.5x6.7x21 (inch)
Weight	45 lbs
Shipping Weight	48 lbs

