



NISSINDO GET TO THE POINT

KP-600 Video / Audio Karaoke Mixer

Specifications

General Functions

- Switches Video and Audio
- Source Input: AUX1, AUX2 and BGM (RCA)
- Microphone Input: 3 front $\frac{1}{4}$ (unbalance) and 2 in rear XLR (balance)
- Key Control: 9-Step Digital Key Controller
- Key control input: 3.55mm (in front panel)
- Digital Echo with Repeat and Time Delay controls
- Enhance the music loudness
- Enhance the Microphone vocal
- Analog stereo Left & Right Audio
- Music Tone adjustment
- Microphone Tone adjustment
- Balance adjustment

Video & Audio Inputs

There are three (3) Inputs, on the rear of the product, labeled

AUX 1 (DVD) Audio and Video RCA female

Audio Sensitivity switch: Low Mid High

Audio signal input: Voltage control potentiometer adjusts the potentiometer ensure signal input of AUX 1 circuit the best situation

AUX 2(CDG) Audio and Video RCA female

Audio Sensitivity switch: Low Mid High

Audio signal input: Voltage control potentiometer adjusts the potentiometer ensure signal input of AUX 2 circuit the best situation

BGM (Back Ground Music) Audio and Video RCA female

Audio Sensitivity switch: Low Mid High

Audio signal input: Voltage control potentiometer adjusts the potentiometer ensure signal input of BGM circuit the best situation

Video & Audio Outputs

There are tow (2) Output, on the rear of the product, labeled

Audio Out 1 Analog stereo Left & Right Audio: RCA female (Left & Right)

Audio Out 2 Analog stereo Left & Right Audio: RCA female (Left & Right)

Audio Effect Analog stereo Left & Right Audio: RCA female out and input terminal

Video Three Output: Analog composite signal RCA female (Yellow color)

Remote Control Status

Remote connector in rear panel

Music Master Volume

Microphone master Volume

Music Enhance

Microphone Enhance

Echo Volume

Input selector: AUX1, AUX2 and BGM or Auto selection

Key Control

Mute

Microphones Connectors

Three (3) 1/4 TRS Input connectors in front panel

Two (2) XLR (F) balance input connector in rear panel

Mechanical

No fan noise

Rack mountable: 2U

Product Size (WxHxD): 17 x 2.5' x 9 inches (excluding ears)

Product Weight: 8 lbs. (excluding external power supply)

Enclosure type: Metal

Product Built-in Rack mountable kit

AC-power: power supply 110V-60 Hz (consume 20w)

Dimension Size

Dimensions (WxHxD): 20.5 x 4.5 x 10 (inches)

Shipping Weight: 9.4 Lbs.